



# AiP74LVC3GU04 Triple Unbuffered Inverter

## Product Specification

### Specification Revision History:

| Version    | Date    | Description           |
|------------|---------|-----------------------|
| 2024-04-A0 | 2024-04 | New                   |
| 2024-07-A1 | 2024-07 | Modify the parameters |
|            |         |                       |
|            |         |                       |



# Contents

|  |           |
|--|-----------|
| <b>1、 General Description.....</b>   | <b>3</b>  |
| <b>2、 Block Diagram And Pin Description .....</b>                                  | <b>5</b>  |
| 2.1、 Block Diagram .....   | 5         |
| 2.2、 Pin Configurations.....   | 5         |
| 2.3、 Pin Description .....   | 5         |
| 2.4、 Function Table.....   | 5         |
| <b>3、 Electrical Parameter .....</b>   | <b>6</b>  |
| 3.1、 Absolute Maximum Ratings.....   | 6         |
| 3.2、 Recommended Operating Conditions.....   | 6         |
| 3.3、 Electrical Characteristics .....  | 7         |
| 3.3.1、 DC Characteristics 1 .....  | 7         |
| 3.3.2、 DC Characteristics 2 .....  | 8         |
| 3.3.3、 AC Characteristics 1 .....  | 8         |
| 3.3.4、 AC Characteristics 2 .....  | 8         |
| <b>4、 Testing Circuit .....</b>  | <b>9</b>  |
| 4.1、 AC Testing Circuit .....  | 9         |
| 4.2、 Test Data .....   | 9         |
| 4.3、 AC Testing Waveforms.....   | 10        |
| 4.4、 Measurement Points .....  | 10        |
| <b>5、 Package Information .....</b>  | <b>11</b> |
| 5.1、 TSSOP8.....   | 11        |
| 5.2、 VSSOP8 .....  | 12        |
| 5.3、 XSON8-1.35*1.....   | 13        |
| 5.4、 XSON8-1.95*1.....   | 14        |
| <b>6、 Statements And Notes .....</b>   | <b>15</b> |
| 6.1、 The name and content of Hazardous substances or Elements in the product ..... | 15        |
| 6.2、 Notes .....   | 15        |



## 1、General Description

The AiP74LVC3GU04 is a triple unbuffered inverter.

The input can be driven from either 3.3V or 5V devices. This feature allows the use of this device in a mixed 3.3V and 5V environment.

### Features:

- Wide supply voltage range from 1.65V to 5.5V
- Inputs accept voltages to 5.5 V
- $\pm 24\text{mA}$  output drive at 3.0V
- High-impedance when  $V_{CC}=0\text{V}$
- Temperature range:  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$
- Packaging information: TSSOP8/VSSOP8/XSON8



## Ordering Information:

### Tube packing specifications:

| Part number         | Packaging form | Marking code | Tube quantity | Boxed tube quantity | Boxed quantity | Notes   |
|---------------------|----------------|--------------|---------------|---------------------|----------------|---|
| AiP74LVC3GU04TA8.TB | TSSOP8         | GJXX         | 100 PCS/tube  | 200 tube/box        | 20000 PCS/box  | Dimensions of plastic enclosure:<br>3.0mm×3.0mm<br>Pin spacing:<br>0.65mm |

### Reel packing specifications:

| Part number         | Packaging form | Marking code | Reel quantity | Boxed reel quantity | Notes  |
|---------------------|----------------|--------------|---------------|---------------------|--|
| AiP74LVC3GU04TA8.TR | TSSOP8         | GJXX         | 3000 PCS/reel | 3000 PCS/box        | Dimensions of plastic enclosure:<br>3.0mm×3.0mm<br>Pin spacing:<br>0.65mm  |
| AiP74LVC3GU04YA8.TR | VSSOP8         | GJXX         | 3000 PCS/reel | 3000 PCS/box        | Dimensions of plastic enclosure:<br>2.3mm×2.0mm<br>Pin spacing:<br>0.50mm  |
| AiP74LVC3GU04EB8.TR | XSON8          | GJXX         | 5000 PCS/reel | 25000 PCS/box       | Dimensions of plastic enclosure:<br>1.35mm×1.0mm<br>Pin spacing:<br>0.35mm |
| AiP74LVC3GU04EC8.TR | XSON8          | GJXX         | 5000 PCS/reel | 25000 PCS/box       | Dimensions of plastic enclosure:<br>1.95mm×1.0mm<br>Pin spacing:<br>0.50mm |

Note 1: "XX" refers to variable content, meaning year and package batch serial number.

Note 2: If the physical information is inconsistent with the ordering information, please refer to the actual product.



## 2、Block Diagram And Pin Description

### 2.1、Block Diagram





Figure 1. Logic symbol

### 2.2、Pin Configurations



### 2.3、Pin Description

| Pin No. | Pin Name        | Description    |
|---------|-----------------|----------------|
| 1       | 1A              | data input     |
| 2       | 3Y              | data output    |
| 3       | 2A              | data input     |
| 4       | GND             | ground (0V)    |
| 5       | 2Y              | data output    |
| 6       | 3A              | data input     |
| 7       | 1Y              | data output    |
| 8       | V <sub>CC</sub> | supply voltage |

### 2.4、Function Table

| Input | Output |
|-------|--------|
| nA    | nY     |
| L     | H      |
| H     | L      |

Note: H=HIGH voltage level; L=LOW voltage level.



## 3、Electrical Parameter

### 3.1、Absolute Maximum Ratings

(Voltages are referenced to GND (ground=0V), unless otherwise specified.)

| Parameter               | Symbol    | Conditions                   | Min. | Max.         | Unit |
|-------------------------|-----------|------------------------------|------|--------------|------|
| supply voltage          | $V_{CC}$  | -                            | -0.5 | +6.5         | V    |
| input voltage           | $V_I$     | -                            | -0.5 | +6.5         | V    |
| output voltage          | $V_O$     | Active mode                  | -0.5 | $V_{CC}+0.5$ | V    |
| supply current          | $I_{CC}$  | -                            | -    | 100          | mA   |
| ground current          | $I_{GND}$ | -                            | -100 | -            | mA   |
| input clamping current  | $I_{IK}$  | $V_I < 0V$                   | -50  | -            | mA   |
| output current          | $I_O$     | $V_O=0V$ to $V_{CC}$         | -    | $\pm 50$     | mA   |
| output clamping current | $I_{OK}$  | $V_O > V_{CC}$ or $V_O < 0V$ | -    | $\pm 50$     | mA   |
| storage temperature     | $T_{stg}$ | -                            | -65  | +150         | °C   |
| soldering temperature   | $T_L$     | 10s                          | 260  |              | °C   |

### 3.2、Recommended Operating Conditions

| Parameter                           | Symbol              | Conditions               | Min. | Typ. | Max.     | Unit |
|-------------------------------------|---------------------|--------------------------|------|------|----------|------|
| supply voltage                      | $V_{CC}$            | -                        | 1.65 | -    | 5.5      | V    |
| input voltage                       | $V_I$               | -                        | 0    | -    | 5.5      | V    |
| output voltage                      | $V_O$               | Active mode              | 0    | -    | $V_{CC}$ | V    |
| ambient temperature                 | $T_{amb}$           | -                        | -40  | -    | +125     | °C   |
| input transition rise and fall rate | $\Delta t/\Delta V$ | $V_{CC}=1.65V$ to $2.7V$ | -    | -    | 20       | ns/V |
|                                     |                     | $V_{CC}=2.7V$ to $5.5V$  | -    | -    | 10       | ns/V |



## 3.3、Electrical Characteristics

### 3.3.1、DC Characteristics 1

( $T_{amb}=-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ , voltages are referenced to GND (ground=0V), unless otherwise specified.)

| Parameter                 | Symbol          | V <sub>CC</sub> | Conditions  | Min.                 | Typ. | Max.                 | Unit |
|---------------------------|-----------------|-----------------|---|----------------------|------|----------------------|------|
| HIGH-level input voltage  | V <sub>IH</sub> | 1.65V to 5.5V   | -   | $0.75 \times V_{CC}$ | -    | -                    | V    |
| LOW-level input voltage   | V <sub>IL</sub> | 1.65V to 5.5V   | -   | -                    | -    | $0.25 \times V_{CC}$ | V    |
| HIGH-level output voltage | V <sub>OH</sub> | 1.65V to 5.5V   | I <sub>O</sub> =-100uA  | $V_{CC} - 0.1$       | -    | -                    | V    |
|                           |                 | 1.65V           | I <sub>O</sub> =-4mA  | 1.2                  | -    | -                    | V    |
|                           |                 | 2.3V            | I <sub>O</sub> =-8mA  | 1.9                  | -    | -                    | V    |
|                           |                 | 2.7V            | I <sub>O</sub> =-12mA   | 2.2                  | -    | -                    | V    |
|                           |                 | 3.0V            | I <sub>O</sub> =-24mA   | 2.3                  | -    | -                    | V    |
|                           |                 | 4.5V            | I <sub>O</sub> =-32mA   | 3.8                  | -    | -                    | V    |
| LOW-level output voltage  | V <sub>OL</sub> | 1.65V to 5.5V   | I <sub>O</sub> =100uA   | -                    | -    | 0.10                 | V    |
|                           |                 | 1.65V           | I <sub>O</sub> =4mA   | -                    | -    | 0.45                 | V    |
|                           |                 | 2.3V            | I <sub>O</sub> =8mA   | -                    | -    | 0.30                 | V    |
|                           |                 | 2.7V            | I <sub>O</sub> =12mA  | -                    | -    | 0.40                 | V    |
|                           |                 | 3.0V            | I <sub>O</sub> =24mA  | -                    | -    | 0.55                 | V    |
|                           |                 | 4.5V            | I <sub>O</sub> =32mA  | -                    | -    | 0.55                 | V    |
| input leakage current     | I <sub>I</sub>  | 0V to 5.5V      | V <sub>I</sub> =5.5V or GND                                   | -                    | -    | ±1                   | uA   |
| supply current            | I <sub>CC</sub> | 1.65V to 5.5V   | V <sub>I</sub> =V <sub>CC</sub> or GND;<br>I <sub>O</sub> =0A | -                    | -    | 4                    | uA   |

Note: All typical values are measured at  $T_{amb}=25^{\circ}\text{C}$ .



### 3.3.2、DC Characteristics 2

( $T_{amb}=-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ , voltages are referenced to GND (ground = 0V), unless otherwise specified.)

| Parameter                 | Symbol               | V <sub>CC</sub> | Conditions   | Min.                  | Typ. | Max.                | Unit |
|---------------------------|----------------------|-----------------|--|-----------------------|------|---------------------|------|
| HIGH-level input voltage  | V <sub>IH</sub>      | 1.65V to 1.95V  | -  | $0.8 \times V_{CC}$   | -    | -                   | V    |
| LOW-level input voltage   | V <sub>IL</sub>      | 1.65V to 1.95V  | -  | -                     | -    | $0.2 \times V_{CC}$ | V    |
| HIGH-level output voltage | V <sub>OH</sub>      | 1.65V to 5.5V   | I <sub>O</sub> =-100uA                                     | V <sub>CC</sub> - 0.1 | -    | -                   | V    |
|                           |                      | 1.65V           | I <sub>O</sub> =-4mA                                       | 0.95                  | -    | -                   | V    |
|                           |                      | 2.3V            | I <sub>O</sub> =-8mA                                       | 1.7                   | -    | -                   | V    |
|                           |                      | 2.7V            | I <sub>O</sub> =-12mA                                      | 1.9                   | -    | -                   | V    |
|                           |                      | 3.0V            | I <sub>O</sub> =-24mA                                      | 2.0                   | -    | -                   | V    |
| LOW-level output voltage  | V <sub>OL</sub>      | 1.65V to 5.5V   | I <sub>O</sub> =100uA                                      | -                     | -    | 0.10                | V    |
|                           |                      | 1.65V           | I <sub>O</sub> =4mA  | -                     | -    | 0.70                | V    |
|                           |                      | 2.3V            | I <sub>O</sub> =8mA  | -                     | -    | 0.45                | V    |
|                           |                      | 2.7V            | I <sub>O</sub> =12mA                                       | -                     | -    | 0.60                | V    |
|                           |                      | 3.0V            | I <sub>O</sub> =24mA                                       | -                     | -    | 0.80                | V    |
| 4.5V                      | I <sub>O</sub> =32mA | -               | -  | 0.80                  | V    |                     |      |
| input leakage current     | I <sub>I</sub>       | 0V to 5.5V      | V <sub>I</sub> =5.5V or GND                                | -                     | -    | ±1                  | uA   |
| supply current            | I <sub>CC</sub>      | 1.65V to 5.5V   | V <sub>I</sub> =V <sub>CC</sub> or GND; I <sub>O</sub> =0A | -                     | -    | 4                   | uA   |

### 3.3.3、AC Characteristics 1

( $T_{amb}=-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ , voltages are referenced to GND (ground = 0V), unless otherwise specified.)

| Parameter                  | Symbol                              | V <sub>CC</sub> | Conditions   | Min. | Typ. | Max. | Unit |
|----------------------------|-------------------------------------|-----------------|--------------|------|------|------|------|
| nA to nY propagation delay | t <sub>PLH</sub> , t <sub>PHL</sub> | 1.65V to 1.95V  | see Figure 3 | -    | 2.3  | 5.0  | ns   |
|                            |                                     | 2.3V to 2.7V    |              | -    | 1.8  | 4.0  | ns   |
|                            |                                     | 2.7V            |              | -    | 2.6  | 4.5  | ns   |
|                            |                                     | 3.0V to 3.6V    |              | -    | 2.3  | 3.7  | ns   |
|                            |                                     | 4.5V to 5.5V    |              | -    | 1.7  | 3.0  | ns   |

Note: Typical values are measured at  $T_{amb}=25^{\circ}\text{C}$  and  $V_{CC}=1.8\text{V}$ , 2.5V, 2.7V, 3.3V and 5.0V respectively.

### 3.3.4、AC Characteristics 2

( $T_{amb}=-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ , voltages are referenced to GND (ground = 0V), unless otherwise specified.)

| Parameter                  | Symbol                              | V <sub>CC</sub> | Conditions   | Min. | Typ. | Max. | Unit |
|----------------------------|-------------------------------------|-----------------|--------------|------|------|------|------|
| nA to nY propagation delay | t <sub>PLH</sub> , t <sub>PHL</sub> | 1.65V to 1.95V  | see Figure 3 | -    | -    | 6.3  | ns   |
|                            |                                     | 2.3V to 2.7V    |              | -    | -    | 4.0  | ns   |
|                            |                                     | 2.7V            |              | -    | -    | 5.6  | ns   |
|                            |                                     | 3.0V to 3.6V    |              | -    | -    | 4.5  | ns   |
|                            |                                     | 4.5V to 5.5V    |              | -    | -    | 3.8  | ns   |



## 4、Testing Circuit

### 4.1、AC Testing Circuit




Figure 2. AC Testing Circuit

Definitions for test circuit:

$R_L$ =Load resistance.

$C_L$ =Load capacitance including jig and probe capacitance.

### 4.2、Test Data

| Supply voltage | Input    |             | Load  |              | $V_{EXT}$         |
|----------------|----------|-------------|-------|--------------|-------------------|
| $V_{CC}$       | $V_I$    | $t_r = t_f$ | $C_L$ | $R_L$        | $t_{PLH}/t_{PHL}$ |
| 1.65V to 1.95V | $V_{CC}$ | $\leq 3ns$  | 30pF  | 1k $\Omega$  | Open              |
| 2.3V to 2.7V   | $V_{CC}$ | $\leq 3ns$  | 30pF  | 500 $\Omega$ | Open              |
| 2.7V           | $V_{CC}$ | $\leq 3ns$  | 50pF  | 500 $\Omega$ | Open              |
| 3.0V to 3.6V   | $V_{CC}$ | $\leq 3ns$  | 50pF  | 500 $\Omega$ | Open              |
| 4.5V to 5.5V   | $V_{CC}$ | $\leq 3ns$  | 50pF  | 500 $\Omega$ | Open              |



## 4.3、AC Testing Waveforms




Figure 3. The data input (A) to output (Y) propagation delays


## 4.4、Measurement Points

| Supply voltage | Input               | Output              |
|----------------|---------------------|---------------------|
| $V_{CC}$       | $V_M$               | $V_M$               |
| 1.65V to 1.95V | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ |
| 2.3V to 2.7V   | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ |
| 2.7V           | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ |
| 3.0V to 3.6V   | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ |
| 4.5V to 5.5V   | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ |



## 5、Package Information


### 5.1、TSSOP8



| 2023/12/A | Dimensions In Millimeters |      |
|-----------|---------------------------|------|
| Symbol    | Min                       | Max  |
| A         | —                         | 1.10 |
| A1        | 0                         | 0.15 |
| A2        | 0.75                      | 0.95 |
| A3        | 0.25                      |      |
| bp        | 0.22                      | 0.38 |
| c         | 0.08                      | 0.18 |
| D         | 2.90                      | 3.10 |
| E         | 2.90                      | 3.10 |
| HE        | 3.90                      | 4.10 |
| L         | 0.50                      |      |
| Lp        | 0.33                      | 0.47 |
| e         | 0.65                      |      |
| Z         | 0.35                      | 0.70 |
| $\theta$  | 0°                        | 8°   |



5.2、VSSOP8




NOTES  
1.0 COP  
DIE ATTA  
2.0 D E

| 2023/12/A | Dimensions In Millimeters |      |
|-----------|---------------------------|------|
| Symbol    | Min                       | Max  |
| A         | —                         | 1.00 |
| A1        | 0.00                      | 0.15 |
| A2        | 0.60                      | 0.85 |
| A3        | 0.12                      |      |
| Q         | 0.19                      | 0.21 |
| b         | 0.17                      | 0.27 |
| c         | 0.08                      | 0.23 |
| D         | 1.90                      | 2.10 |
| E         | 2.20                      | 2.40 |
| HE        | 3.00                      | 3.20 |
| HE1       | 3.00                      | 3.40 |
| e         | 0.50                      |      |
| L         | 0.40                      |      |
| L1        | 0.15                      | 0.40 |
| Y         | 0.10                      |      |
| Z         | 0.10                      | 0.40 |
| $\theta$  | 0°                        | 8°   |




## 5.3、XSON8-1.35\*1



| 2023/12/A | Dimensions In Millimeters |       |       |
|-----------|---------------------------|-------|-------|
|           | Symbol                    | Min   | Max   |
|           | A                         | 0.28  | 0.32  |
|           | A1                        | 0.00  | 0.05  |
|           | A3                        | 0.10  |       |
|           | b                         | 0.11  | 0.21  |
|           | D                         | 1.35  |       |
|           | E                         | 1.00  |       |
|           | e                         | 0.35  |       |
|           | L                         | 0.25  | 0.35  |
|           | L1                        | 0.275 | 0.475 |
|           | L2                        | 0.30  | 0.40  |
|           | L3                        | 0.325 | 0.525 |



## 5.4、XSON8-1.95\*1



| 2023/12/A<br>Symbol | Dimensions In Millimeters |      |
|---------------------|---------------------------|------|
|                     | Min                       | Max  |
| A                   | 0.45                      | 0.55 |
| A1                  | 0                         | 0.05 |
| A3                  | 0.127                     |      |
| b                   | 0.15                      | 0.25 |
| D                   | 1.95                      |      |
| E                   | 1.00                      |      |
| e                   | 0.50                      |      |
| L                   | 0.25                      | 0.35 |
| L1                  | 0.25                      | 0.45 |
| L2                  | 0.30                      | 0.40 |
| L3                  | 0.30                      | 0.50 |



## 6、 Statements And Notes

### 6.1、 The name and content of Hazardous substances or Elements in the product

| Part name               | Hazardous substances or Elements  |                               |                               |                               |                          |                                |                   |                       |                           |                      |
|-------------------------|---|-------------------------------|-------------------------------|-------------------------------|--------------------------|--------------------------------|-------------------|-----------------------|---------------------------|----------------------|
|                         | Lead and lead compounds   | Mercury and mercury compounds | Cadmium and cadmium compounds | Hexavalent chromium compounds | Polybrominated biphenyls | Polybrominated biphenyl ethers | Dibutyl phthalate | Butylbenzyl phthalate | Di-2-ethylhexyl phthalate | Diisobutyl phthalate |
| Lead frame              | ○   | ○                             | ○                             | ○                             | ○                        | ○                              | ○                 | ○                     | ○                         | ○                    |
| Plastic resin           | ○   | ○                             | ○                             | ○                             | ○                        | ○                              | ○                 | ○                     | ○                         | ○                    |
| Chip                    | ○   | ○                             | ○                             | ○                             | ○                        | ○                              | ○                 | ○                     | ○                         | ○                    |
| The lead                | ○   | ○                             | ○                             | ○                             | ○                        | ○                              | ○                 | ○                     | ○                         | ○                    |
| Plastic sheet installed | ○   | ○                             | ○                             | ○                             | ○                        | ○                              | ○                 | ○                     | ○                         | ○                    |
| explanation             | ○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard.<br>×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements. |                               |                               |                               |                          |                                |                   |                       |                           |                      |

### 6.2、 Notes

We recommend you to read this chapter carefully before using this product.

The information in this chapter is provided for reference only and i-Core disclaims any express or implied warranties, including but not limited to applicability, special application or non-infringement of third party rights.

This product is not suitable for critical equipment such as life-saving, life-sustaining or safety equipment. It is also not suitable for applications that may result in personal injury, death, or serious property or environmental damage due to product malfunction or failure. I-Core will not be liable for any damages incurred by the customers at their own risk for such applications.

The customer is responsible for conducting all necessary tests i-Core's application to avoid failure in the application or the application of the customer's third party users. I-Core does not accept any liability.

The Company reserves the right to change or improve the information published in this chapter at any time. The information in this chapter are subject to change without notice. We recommend the customer to consult our sales staff before purchasing.

Please obtain related materials form i-Core's regular channels and we are not responsible for its content if it is provided by sources other than our company.

In case of any conflict between the Chinese and English version, the version is subject to the Chinese one.