



AiP74AUP1G332

Single 3-Input Or Gate

Product Specification

Specification Revision History:

Version	Date	Description
2025-09-A0	2025-09	New
2025-11-A1	2025-11	Modify the parameters



Contents

1、General Description.....	1
2、Block Diagram And Pin Description	2
2.1、Block Diagram	2
2.2、Pin Configurations.....	2
2.3、Pin Description.....	2
2.4、Function Table.....	3
3、Electrical Parameter	3
3.1、Absolute Maximum Ratings.....	3
3.2、Recommended Operating Conditions.....	3
3.3、Electrical Characteristics.....	4
3.3.1、DC Characteristics 1	4
3.3.2、DC Characteristics 2	5
3.3.3、DC Characteristics 3.....	6
3.3.4、AC Characteristics 1	7
3.3.5、AC Characteristics 2.....	8
3.3.6、AC Characteristics 3.....	9
4、Testing Circuit	10
4.1、AC Testing Circuit	10
4.2、AC Testing Waveforms.....	10
4.3、Measurement Points	10
4.4、Test Data	10
5、Package Information	11
5.1、XSON6(1*1.45)-0.5	11
5.2、XSON6(1*1)-0.35.....	12
5.3、SOT23-6.....	13
5.4、SOT363.....	14
6、Statements And Notes	15
6.1、The name and content of Hazardous substances or Elements in the product.....	15
6.2、Notes	15



1、General Description

The AiP74AUP1G332 provides a single 3-input OR gate.

This device ensures a very low static and dynamic power consumption across the entire V_{CC} range from 0.8V to 3.6V.

Features:

- Wide supply voltage range from 0.8V to 3.6V
- Low static power consumption; $I_{CC}=1\mu A$ (maximum)
- Inputs accept voltages up to 3.6V
- Specified from $-40^{\circ}C$ to $+125^{\circ}C$
- Packaging information: XSON6/SOT23-6/SOT363

Ordering Information:

Part number	Packaging form	Marking code	Reel quantity	Boxed reel quantity	Notes
AiP74AUP1G332 GB236.TR	SOT23-6	AiP JL	3000 PCS/reel	30000 PCS/box	Dimensions of plastic enclosure: 2.9mm×1.6mm Pin spacing: 0.95mm
AiP74AUP1G332 GC363.TR	SOT363	JLXX	3000 PCS/reel	30000 PCS/box	Dimensions of plastic enclosure: 2.1mm×1.3mm Pin spacing: 0.65mm
AiP74AUP1G332 EA6.TR	XSON6	JL XX	5000 PCS/reel	25000 PCS/box	Dimensions of plastic enclosure: 1.45mm×1.0mm Pin spacing: 0.50mm
AiP74AUP1G332 ED6.TR	XSON6	JL XX	5000 PCS/reel	25000 PCS/box	Dimensions of plastic enclosure: 1.0mm×1.0mm Pin spacing: 0.35mm

Note 1: “XX” refers to variable content, meaning package batch serial number.

Note 2: If the physical information is inconsistent with the ordering information, please refer to the actual product.



2、Block Diagram And Pin Description

2.1、Block Diagram




Figure 1. Logic symbol





Figure 2. Logic diagram

2.2、Pin Configurations



2.3、Pin Description

Pin No.	Pin Name	Description
1	A	data input A
2	GND	ground (0V)
3	B	data input B
4	Y	data output Y
5	V _{CC}	supply voltage
6	C	data input C



2.4、Function Table

Input			Output
A	B	C	Y
H	X	X	H
X	H	X	H
X	X	H	H
L	L	L	L

Note: H=HIGH voltage level; L=LOW voltage level; X=Don't care.

3、Electrical Parameter

3.1、Absolute Maximum Ratings

($T_{amb}=25^{\circ}\text{C}$, all voltage referenced to GND (ground=0V), unless otherwise specified)

Characteristic	Symbol	Conditions	Min.	Max.	Unit
supply voltage	V_{CC}	-	-0.5	+4.6	V
input clamping current	I_{IK}	$V_I < 0\text{V}$	-50	-	mA
input voltage	V_I	[1]	-0.5	+4.6	V
output clamping current	I_{OK}	$V_O < 0\text{V}$	-50	-	mA
output voltage	V_O	Active mode ^[1]	-0.5	$V_{CC}+0.5$	V
		Power-down mode ^[1]	-0.5	+4.6	V
output current	I_O	$V_O=0\text{V}$ to V_{CC}	-	± 20	mA
supply current	I_{CC}	-	-	+50	mA
ground current	I_{GND}	-	-50	-	mA
storage temperature	T_{stg}	-	-65	+150	$^{\circ}\text{C}$
total power dissipation	P_{tot}	-	-	250	mW
soldering temperature	T_L	10s	260		$^{\circ}\text{C}$
Electrostatic discharge	ESD	HBM	8000		V

Note:

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

3.2、Recommended Operating Conditions

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V_{CC}	-	0.8	-	3.6	V
input voltage	V_I	-	0	-	3.6	V
output voltage	V_O	Active mode	0	-	V_{CC}	V
		Power-down mode; $V_{CC}=0\text{V}$	0	-	3.6	V
ambient temperature	T_{amb}	-	-40	-	+125	$^{\circ}\text{C}$



3.3、Electrical Characteristics

3.3.1、DC Characteristics 1

($T_{amb}=25^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	$V_{CC}=0.8\text{V}$		0.72	-	-	V
		$V_{CC}=0.9\text{V to }1.95\text{V}$		$0.75 \times V_{CC}$	-	-	V
		$V_{CC}=2.3\text{V to }2.7\text{V}$		1.6	-	-	V
		$V_{CC}=3.0\text{V to }3.6\text{V}$		2.0	-	-	V
LOW-level input voltage	V_{IL}	$V_{CC}=0.8\text{V}$		-	-	$0.30 \times V_{CC}$	V
		$V_{CC}=0.9\text{V to }1.95\text{V}$		-	-	$0.35 \times V_{CC}$	V
		$V_{CC}=2.3\text{V to }2.7\text{V}$		-	-	0.7	V
		$V_{CC}=3.0\text{V to }3.6\text{V}$		-	-	0.9	V
HIGH-level output voltage	V_{OH}	$V_I=V_{IH} \text{ or } V_{IL}$	$I_O=-20\mu\text{A}; V_{CC}=0.8\text{V to }3.6\text{V}$	$V_{CC}-0.1$	-	-	V
			$I_O=-1.1\text{mA}; V_{CC}=1.1\text{V}$	$0.75 \times V_{CC}$	-	-	V
			$I_O=-1.7\text{mA}; V_{CC}=1.4\text{V}$	1.11	-	-	V
			$I_O=-1.9\text{mA}; V_{CC}=1.65\text{V}$	1.32	-	-	V
			$I_O=-2.3\text{mA}; V_{CC}=2.3\text{V}$	2.05	-	-	V
			$I_O=-3.1\text{mA}; V_{CC}=2.3\text{V}$	1.9	-	-	V
			$I_O=-2.7\text{mA}; V_{CC}=3.0\text{V}$	2.72	-	-	V
			$I_O=-4.0\text{mA}; V_{CC}=3.0\text{V}$	2.6	-	-	V
LOW-level output voltage	V_{OL}	$V_I=V_{IH} \text{ or } V_{IL}$	$I_O=20\mu\text{A}; V_{CC}=0.8\text{V to }3.6\text{V}$	-	-	0.1	V
			$I_O=1.1\text{mA}; V_{CC}=1.1\text{V}$	-	-	$0.3 \times V_{CC}$	V
			$I_O=1.7\text{mA}; V_{CC}=1.4\text{V}$	-	-	0.31	V
			$I_O=1.9\text{mA}; V_{CC}=1.65\text{V}$	-	-	0.31	V
			$I_O=2.3\text{mA}; V_{CC}=2.3\text{V}$	-	-	0.31	V
			$I_O=3.1\text{mA}; V_{CC}=2.3\text{V}$	-	-	0.44	V
			$I_O=2.7\text{mA}; V_{CC}=3.0\text{V}$	-	-	0.31	V
			$I_O=4.0\text{mA}; V_{CC}=3.0\text{V}$	-	-	0.44	V
input leakage current	I_I	$V_I=\text{GND to }3.6\text{V}; V_{CC}=0\text{V to }3.6\text{V}$		-	-	± 1	μA
power-off leakage current	I_{OFF}	$V_I \text{ or } V_O=0\text{V to }3.6\text{V}; V_{CC}=0\text{V}$		-	-	± 1	μA
additional power-off leakage current	ΔI_{OFF}	$V_I \text{ or } V_O=0\text{V to }3.6\text{V}; V_{CC}=0\text{V to }0.2\text{V}$		-	-	± 1	μA
supply current	I_{CC}	$V_I=\text{GND or }V_{CC}; I_O=0\text{A}; V_{CC}=0.8\text{V to }3.6\text{V}$		-	-	1	μA
additional supply current	ΔI_{CC}	$V_I=V_{CC}-0.6\text{V}; I_O=0\text{A}; V_{CC}=3.3\text{V}^{[1]}$		-	-	40	μA

Note:

[1] One input at $V_{CC}-0.6\text{V}$, other input at V_{CC} or GND.



3.3.2、DC Characteristics 2

($T_{amb}=-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V _{IH}	V _{CC} =0.8V		0.72	-	-	V
		V _{CC} =0.9V to 1.95V		0.75×V _{CC}	-	-	V
		V _{CC} =2.3V to 2.7V		1.6	-	-	V
		V _{CC} =3.0V to 3.6V		2.0	-	-	V
LOW-level input voltage	V _{IL}	V _{CC} =0.8V		-	-	0.30×V _{CC}	V
		V _{CC} =0.9V to 1.95V		-	-	0.35×V _{CC}	V
		V _{CC} =2.3V to 2.7V		-	-	0.7	V
		V _{CC} =3.0V to 3.6V		-	-	0.9	V
HIGH-level output voltage	V _{OH}	V _I =V _{IH} or V _{IL}	I _O =-20uA; V _{CC} =0.8V to 3.6V	V _{CC} -0.1	-	-	V
			I _O =-1.1mA; V _{CC} =1.1V	0.7×V _{CC}	-	-	V
			I _O =-1.7mA; V _{CC} =1.4V	1.03	-	-	V
			I _O =-1.9mA; V _{CC} =1.65V	1.30	-	-	V
			I _O =-2.3mA; V _{CC} =2.3V	1.97	-	-	V
			I _O =-3.1mA; V _{CC} =2.3V	1.85	-	-	V
			I _O =-2.7mA; V _{CC} =3.0V	2.67	-	-	V
			I _O =-4.0mA; V _{CC} =3.0V	2.55	-	-	V
LOW-level output voltage	V _{OL}	V _I =V _{IH} or V _{IL}	I _O =20uA; V _{CC} =0.8V to 3.6V	-	-	0.1	V
			I _O =1.1mA; V _{CC} =1.1V	-	-	0.3×V _{CC}	V
			I _O =1.7mA; V _{CC} =1.4V	-	-	0.37	V
			I _O =1.9mA; V _{CC} =1.65V	-	-	0.35	V
			I _O =2.3mA; V _{CC} =2.3V	-	-	0.33	V
			I _O =3.1mA; V _{CC} =2.3V	-	-	0.45	V
			I _O =2.7mA; V _{CC} =3.0V	-	-	0.33	V
			I _O =4.0mA; V _{CC} =3.0V	-	-	0.45	V
input leakage current	I _I	V _I =GND to 3.6V; V _{CC} =0V to 3.6V		-	-	±2	uA
power-off leakage current	I _{OFF}	V _I or V _O =0V to 3.6V; V _{CC} =0V		-	-	±2	uA
additional power-off leakage current	ΔI _{OFF}	V _I or V _O =0V to 3.6V; V _{CC} =0V to 0.2V		-	-	±2	uA
supply current	I _{CC}	V _I =GND or V _{CC} ; I _O =0A; V _{CC} =0.8V to 3.6V		-	-	2	uA
additional supply current	ΔI _{CC}	V _I =V _{CC} -0.6V; I _O =0A; V _{CC} =3.3V ^[1]		-	-	50	uA

Note:

[1] One input at $V_{CC}-0.6\text{V}$, other input at V_{CC} or GND.



3.3.3、DC Characteristics 3

($T_{amb} = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V _{IH}	V _{CC} =0.8V		0.75	-	-	V
		V _{CC} =0.9V to 1.95V		0.80×V _{CC}	-	-	V
		V _{CC} =2.3V to 2.7V		1.6	-	-	V
		V _{CC} =3.0V to 3.6V		2.0	-	-	V
LOW-level input voltage	V _{IL}	V _{CC} =0.8V		-	-	0.25×V _{CC}	V
		V _{CC} =0.9V to 1.95V		-	-	0.30×V _{CC}	V
		V _{CC} =2.3V to 2.7V		-	-	0.7	V
		V _{CC} =3.0V to 3.6V		-	-	0.9	V
HIGH-level output voltage	V _{OH}	V _I =V _{IH} or V _{IL}	I _O =-20uA; V _{CC} =0.8V to 3.6V	V _{CC} -0.11	-	-	V
			I _O =-1.1mA; V _{CC} =1.1V	0.6×V _{CC}	-	-	V
			I _O =-1.7mA; V _{CC} =1.4V	0.93	-	-	V
			I _O =-1.9mA; V _{CC} =1.65V	1.17	-	-	V
			I _O =-2.3mA; V _{CC} =2.3V	1.77	-	-	V
			I _O =-3.1mA; V _{CC} =2.3V	1.67	-	-	V
			I _O =-2.7mA; V _{CC} =3.0V	2.40	-	-	V
			I _O =-4.0mA; V _{CC} =3.0V	2.30	-	-	V
LOW-level output voltage	V _{OL}	V _I =V _{IH} or V _{IL}	I _O =20uA; V _{CC} =0.8V to 3.6V	-	-	0.11	V
			I _O =1.1mA; V _{CC} =1.1V	-	-	0.33×V _{CC}	V
			I _O =1.7mA; V _{CC} =1.4V	-	-	0.41	V
			I _O =1.9mA; V _{CC} =1.65V	-	-	0.39	V
			I _O =2.3mA; V _{CC} =2.3V	-	-	0.36	V
			I _O =3.1mA; V _{CC} =2.3V	-	-	0.50	V
			I _O =2.7mA; V _{CC} =3.0V	-	-	0.36	V
			I _O =4.0mA; V _{CC} =3.0V	-	-	0.50	V
input leakage current	I _I	V _I =GND to 3.6V; V _{CC} =0V to 3.6V		-	-	±4	uA
power-off leakage current	I _{OFF}	V _I or V _O =0V to 3.6V; V _{CC} =0V		-	-	±4	uA
additional power-off leakage current	ΔI _{OFF}	V _I or V _O =0V to 3.6V; V _{CC} =0V to 0.2V		-	-	±4	uA
supply current	I _{CC}	V _I =GND or V _{CC} ; I _O =0A; V _{CC} =0.8V to 3.6V		-	-	4	uA
additional supply current	ΔI _{CC}	V _I =V _{CC} -0.6V; I _O =0A; V _{CC} =3.3V ^[1]		-	-	75	uA

Note:

[1] One input at $V_{CC}-0.6\text{V}$, other input at V_{CC} or GND.



3.3.4、AC Characteristics 1

($T_{amb}=25^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ. ^[1]	Max.	Unit
propagation delay	t_{PLH}, t_{PHL}	A, B or C to Y; see Figure 4	$C_L=5\text{pF}$			
			$V_{CC}=0.8\text{V}$	-	17.6	- ns
			$V_{CC}=1.1\text{V to }1.3\text{V}$	2.3	5.2	10.2 ns
			$V_{CC}=1.4\text{V to }1.6\text{V}$	1.7	3.7	6.0 ns
			$V_{CC}=1.65\text{V to }1.95\text{V}$	1.6	3.0	4.7 ns
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.4	2.3	3.3 ns
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.2	2.1	2.9 ns
			$C_L=10\text{pF}$			
			$V_{CC}=0.8\text{V}$	-	17.6	- ns
			$V_{CC}=1.1\text{V to }1.3\text{V}$	2.5	6.1	11.9 ns
			$V_{CC}=1.4\text{V to }1.6\text{V}$	2.2	4.3	7.1 ns
			$V_{CC}=1.65\text{V to }1.95\text{V}$	2.1	3.5	5.4 ns
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.7	2.9	4.0 ns
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.5	2.6	3.7 ns
			$C_L=15\text{pF}$			
			$V_{CC}=0.8\text{V}$	-	23.6	- ns
			$V_{CC}=1.1\text{V to }1.3\text{V}$	2.9	6.9	13.5 ns
			$V_{CC}=1.4\text{V to }1.6\text{V}$	2.5	4.9	7.8 ns
			$V_{CC}=1.65\text{V to }1.95\text{V}$	2.2	4.0	6.2 ns
			$V_{CC}=2.3\text{V to }2.7\text{V}$	2.0	3.3	4.7 ns
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.9	3.1	4.2 ns
			$C_L=30\text{pF}$			
			$V_{CC}=0.8\text{V}$	-	36.3	- ns
			$V_{CC}=1.1\text{V to }1.3\text{V}$	3.6	9.2	17.9 ns
			$V_{CC}=1.4\text{V to }1.6\text{V}$	3.2	6.4	10.4 ns
			$V_{CC}=1.65\text{V to }1.95\text{V}$	3.0	5.3	8.3 ns
			$V_{CC}=2.3\text{V to }2.7\text{V}$	2.8	4.4	6.2 ns
			$V_{CC}=3.0\text{V to }3.6\text{V}$	2.6	4.2	5.5 ns

Note:

[1] All typical values are measured at nominal V_{CC} .



3.3.5、AC Characteristics 2

($T_{amb}=-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
propagation delay	t_{PLH} , t_{PHL}	A, B or C to Y; see Figure 4	$C_L=5\text{pF}$			
			$V_{CC}=0.8\text{V}$	-	-	ns
			$V_{CC}=1.1\text{V to }1.3\text{V}$	2.0	-	10.3
			$V_{CC}=1.4\text{V to }1.6\text{V}$	1.9	-	6.4
			$V_{CC}=1.65\text{V to }1.95\text{V}$	1.4	-	5.2
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.2	-	3.7
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.1	-	3.1
			$C_L=10\text{pF}$			
			$V_{CC}=0.8\text{V}$	-	-	ns
			$V_{CC}=1.1\text{V to }1.3\text{V}$	2.4	-	12.0
			$V_{CC}=1.4\text{V to }1.6\text{V}$	2.0	-	7.3
			$V_{CC}=1.65\text{V to }1.95\text{V}$	1.9	-	5.8
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.5	-	4.5
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.4	-	3.9
			$C_L=15\text{pF}$			
			$V_{CC}=0.8\text{V}$	-	-	ns
			$V_{CC}=1.1\text{V to }1.3\text{V}$	2.7	-	13.6
			$V_{CC}=1.4\text{V to }1.6\text{V}$	2.4	-	8.5
			$V_{CC}=1.65\text{V to }1.95\text{V}$	2.1	-	6.8
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.6	-	5.2
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.7	-	4.5
			$C_L=30\text{pF}$			
			$V_{CC}=0.8\text{V}$	-	-	ns
			$V_{CC}=1.1\text{V to }1.3\text{V}$	3.5	-	18.4
			$V_{CC}=1.4\text{V to }1.6\text{V}$	3.3	-	11.4
			$V_{CC}=1.65\text{V to }1.95\text{V}$	2.9	-	9.1
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.6	-	6.7
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.4	-	6.4



3.3.6、AC Characteristics 3

($T_{amb} = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
propagation delay	t_{PLH}, t_{PHL}	A, B or C to Y; see Figure 4	$C_L = 5\text{pF}$			
			$V_{CC} = 0.8\text{V}$	-	-	ns
			$V_{CC} = 1.1\text{V to } 1.3\text{V}$	-	-	10.3 ns
			$V_{CC} = 1.4\text{V to } 1.6\text{V}$	-	-	6.6 ns
			$V_{CC} = 1.65\text{V to } 1.95\text{V}$	-	-	5.4 ns
			$V_{CC} = 2.3\text{V to } 2.7\text{V}$	-	-	3.9 ns
			$V_{CC} = 3.0\text{V to } 3.6\text{V}$	-	-	3.3 ns
			$C_L = 10\text{pF}$			
			$V_{CC} = 0.8\text{V}$	-	-	ns
			$V_{CC} = 1.1\text{V to } 1.3\text{V}$	-	-	12.0 ns
			$V_{CC} = 1.4\text{V to } 1.6\text{V}$	-	-	7.6 ns
			$V_{CC} = 1.65\text{V to } 1.95\text{V}$	-	-	6.1 ns
			$V_{CC} = 2.3\text{V to } 2.7\text{V}$	-	-	4.7 ns
			$V_{CC} = 3.0\text{V to } 3.6\text{V}$	-	-	4.1 ns
			$C_L = 15\text{pF}$			
			$V_{CC} = 0.8\text{V}$	-	-	ns
			$V_{CC} = 1.1\text{V to } 1.3\text{V}$	-	-	13.6 ns
			$V_{CC} = 1.4\text{V to } 1.6\text{V}$	-	-	8.8 ns
			$V_{CC} = 1.65\text{V to } 1.95\text{V}$	-	-	7.1 ns
			$V_{CC} = 2.3\text{V to } 2.7\text{V}$	-	-	5.4 ns
			$V_{CC} = 3.0\text{V to } 3.6\text{V}$	-	-	4.8 ns
			$C_L = 30\text{pF}$			
			$V_{CC} = 0.8\text{V}$	-	-	ns
			$V_{CC} = 1.1\text{V to } 1.3\text{V}$	-	-	18.7 ns
			$V_{CC} = 1.4\text{V to } 1.6\text{V}$	-	-	11.9 ns
			$V_{CC} = 1.65\text{V to } 1.95\text{V}$	-	-	9.6 ns
			$V_{CC} = 2.3\text{V to } 2.7\text{V}$	-	-	7.1 ns
			$V_{CC} = 3.0\text{V to } 3.6\text{V}$	-	-	6.7 ns



4、Testing Circuit

4.1、AC Testing Circuit




Figure 3. Test circuit for measuring switching times

Definitions for test circuit:

R_L =Load resistance.

C_L =Load capacitance including jig and probe capacitance.

R_T =Termination resistance should be equal to the output impedance Z_o of the pulse generator.

V_{EXT} =External voltage for measuring switching times.

4.2、AC Testing Waveforms




Figure 4. The data input (A, B or C) to output (Y) propagation delays

4.3、Measurement Points

Supply voltage	Input			Output
V_{CC}	V_M	V_I	$t_r=t_f$	V_M
0.8V to 3.6V	$0.5 \times V_{CC}$	V_{CC}	$\leq 3.0\text{ns}$	$0.5 \times V_{CC}$

4.4、Test Data

Supply voltage	Load		V_{EXT}		
V_{CC}	C_L	$R_L^{[1]}$	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}
0.8V to 3.6V	5pF, 10pF, 15pF and 30pF	5kΩ or 1MΩ	open	GND	$2 \times V_{CC}$


Note:

[1] For measuring enable and disable times $R_L=5\text{k}\Omega$, for measuring propagation delays, setup and hold times and pulse width $R_L=1\text{M}\Omega$.



5、Package Information


5.1、XSON6(1*1.45)-0.5



2023/12/A	Dimensions In Millimeters	
Symbol	Min	Max
A	0.51	0.60
A1	0.00	0.05
A3	0.15	
b	0.15	0.25
D	1.45	
E	1.00	
e	0.50	
L	0.25	0.45






5.2、XSON6(1*1)-0.35



2025/03/B	Dimensions In Millimeters	
Symbol	Min	Max
A	0.32	0.50
A1	0	0.05
A3	0.1-0.13 REF	
b	0.10	0.21
D	1.00	
E	1.00	
e	0.35	
L	0.25	0.36
L1	0.30	0.41
L2	0.02	0.12




5.3、SOT23-6



2023/12/A	Dimensions In Millimeters	
Symbol	Min.	Max.
A	—	1.25
A1	0.00	0.12
A2	1.00	1.20
b	0.30	0.50
c	0.10	0.20
D	2.82	3.02
E	2.60	3.00
E1	1.50	1.70
e	0.95	
e1	1.80	2.00
L	0.30	0.60
θ	0°	8°



5.4、SOT363



2023/12/A	Dimensions In Millimeters	
Symbol	Min.	Max.
A	0.90	1.10
A1	0.00	0.10
A2	0.90	1.00
b	0.15	0.35
c	0.11	0.175
D	2.00	2.20
E1	2.15	2.45
E	1.15	1.35
e	0.65	
e1	1.20	1.40
L	0.26	0.46
L1	0.525	
θ	0°	8°



6、Statements And Notes

6.1、The name and content of Hazardous substances or Elements in the product

Part name	Hazardous substances or Elements									
	Lead and lead compounds	Mercury and mercury compounds	Cadmium and cadmium compounds	Hexavalent chromium compounds	Polybrominated biphenyls	Polybrominated biphenyl ethers	Dibutyl phthalate	Butylbenzyl phthalate	Di-2-ethylhexyl phthalate	Diisobutyl phthalate
Lead frame	○	○	○	○	○	○	○	○	○	○
Plastic resin	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
The lead	○	○	○	○	○	○	○	○	○	○
Plastic sheet installed	○	○	○	○	○	○	○	○	○	○
explanation	○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard. ×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements.									

6.2、Notes

We recommend you to read this chapter carefully before using this product.

The information in this chapter is provided for reference only and i-Core disclaims any express or implied warranties, including but not limited to applicability, special application or non-infringement of third party rights.

This product is not suitable for critical equipment such as life-saving, life-sustaining or safety equipment. It is also not suitable for applications that may result in personal injury, death, or serious property or environmental damage due to product malfunction or failure. I-Core will not be liable for any damages incurred by the customers at their own risk for such applications.

The customer is responsible for conducting all necessary tests i-Core's application to avoid failure in the application or the application of the customer's third party users. I-Core does not accept any liability.

The Company reserves the right to change or improve the information published in this chapter at any time. The information in this chapter are subject to change without notice. We recommend the customer to consult our sales staff before purchasing.

Please obtain related materials from i-Core's regular channels and we are not responsible for its content if it is provided by sources other than our company.

In case of any conflict between the Chinese and English version, the version is subject to the Chinese one.